





POWRÓT DO STRONY GŁÓWNEJ



# Koło łańcuchowe z utwardzonymi zębami dla łańcucha rolkowego DIN 8187/ISO R606

Materiał  
**Stal C 43**



## 3/8" x 7/32" (06B-1)

Kod	Ilość zębów <b>z</b>	D1	de	dp	dm	A
T 78914	13	10	43.5	39.80	28	25
T 79166	14	10	46.5	42.80	31	25
T 79167	15	10	49.5	45.81	34	25
T 79168	16	10	52.5	48.82	37	28
T 79169	17	10	55.5	51.83	40	28
T 79170	18	10	58.6	54.85	43	28
T 79171	19	10	61.6	57.87	45	28
T 79172	20	10	64.6	60.89	46	28
T 79173	21	12	67.6	63.91	48	28
T 79174	22	12	70.6	66.93	50	28
T 79175	23	12	73.7	69.95	52	28
T 79176	24	12	76.7	72.97	54	28
T 79177	25	12	79.7	76.00	57	28
T 79178	30	12	94.8	92.12	60	30

## 1/2" x 5/16" (08B-1)

Kod	Ilość zębów <b>z</b>	D1	de	dp	dm	A
T 79179	12	10	53.9	49.07	33	28
T 79190	13	10	57.9	53.06	37	28
T 79193	14	10	61.9	57.07	41	28
T 79194	15	10	65.9	61.09	45	28
T 79196	16	12	69.9	65.10	50	28
T 79198	17	12	74.0	69.11	52	28
T 79200	18	12	78.0	73.14	56	28
T 79201	19	12	82.0	77.16	60	28
T 79202	20	12	86.0	81.19	64	28
T 79203	21	14	90.1	85.22	68	28
T 79204	22	14	94.1	89.24	70	28
T 79205	23	14	98.1	93.27	70	28
T 79206	24	14	102.1	97.29	70	28
T 79208	25	14	106.2	101.33	70	28
T 79209	30	16	126.3	121.50	80	30

	B1	r3	C
06B-1	5.3	10	1.0
08B-1	7.2	13	1.3


Rozmiary w mm.

### **UWAGA:**

Indukcyjnie utwardzone zęby (HRC50).

**Koło łańcuchowe z utwardzonymi zębami  
dla łańcucha rolkowego DIN 8187/ISO R606**

Materiał  
**Stal C 43**



**5/8" x 3/8" (10B-1)**

Kod	Ilość zębów z	D1	de	dp	dm	A
T 79211	12	12	68.2	61.34	42	30
T 79218	13	12	73.2	66.32	47	30
T 79219	14	12	78.2	71.34	52	30
T 79220	15	12	83.2	76.36	57	30
T 79221	16	12	88.3	81.37	60	30
T 79222	17	12	93.3	86.39	60	30
T 79223	18	14	98.3	91.42	70	30
T 79224	19	14	103.3	96.45	70	30
T 79225	20	14	108.4	101.49	75	30
T 79226	21	16	113.4	106.52	75	30
T 79227	22	16	118.4	111.55	80	30
T 79228	23	16	123.5	116.58	80	30
T 79229	24	16	128.5	121.62	80	30
T 79230	25	16	133.6	126.66	80	30
T 79231	30	20	158.8	151.87	90	35

**3/4" x 7/16" (12B-1)**

Kod	Ilość zębów z	D1	de	dp	dm	A
T 79232	12	16	81.8	73.6	52	35
T 79233	13	16	87.8	79.59	58	35
T 79234	14	16	93.8	85.61	64	35
T 79235	15	16	99.8	91.63	70	35
T 79236	16	16	105.8	97.65	75	35
T 79237	17	16	111.9	103.67	80	35
T 79238	18	16	117.9	109.71	80	35
T 79239	19	16	123.9	115.75	80	35
T 79240	20	16	130.0	121.78	80	35
T 79241	21	20	136.0	127.82	90	40
T 79242	22	20	142.0	133.86	90	40
T 79243	23	20	148.1	139.90	90	40
T 79244	24	20	154.1	145.94	90	40
T 79245	25	20	160.2	152.00	90	40
T 79246	30	20	190.4	182.25	95	40

	B1	r3	C
10B-1	9.1	16	1.6
12B-1	11.1	19	2.0


Rozmiary w mm.

**UWAGA:**

Indukcyjnie utwardzone zęby (HRC50).

**Koło łańcuchowe z utwardzonymi zębami  
dla łańcucha rolkowego DIN 8187/ISO R606**

Materiał  
**Stal C 43**



**1" x 17.02" (16B-1)**

Kod	Ilość zębów <b>z</b>	D1	de	dp	dm	A
T 79247	12	16	109.7	98.14	69	40
T 79249	13	16	117.7	106.12	78	40
T 79250	14	16	125.7	114.15	84	40
T 79251	15	16	133.7	122.17	92	40
T 79252	16	20	141.8	130.20	100	45
T 79253	17	20	149.8	138.22	100	45
T 79254	18	20	157.8	146.28	100	45
T 79255	19	20	165.9	154.33	100	45
T 79256	20	20	173.9	162.38	100	45
T 79257	21	20	182.0	170.43	110	50
T 79258	22	20	190.1	178.48	110	50
T 79259	23	20	198.1	186.53	110	50
T 79260	24	20	206.1	194.59	110	50
T 79261	25	20	214.2	202.65	110	50
<b>T 79262</b>	<b>30</b>	<b>20</b>	<b>254.6</b>	<b>243.00</b>	<b>120</b>	<b>50</b>

	B1	r3	C
<b>16B-1</b>	16.2	26	2.5

Rozmiary w mm.

**UWAGA:**

Indukcyjnie utwardzone zęby (HRC50).